

EPA Form 8700-22 (Rev. 9-88) Previous editions are obsolete.

Material Safety Data Sheet

F006 Recyclable Material (Filter Cake)

Recycler's Facility Name and Site Address:

World Resources Company
8113 West Sherman Street
Phoenix, Arizona 85043
Tele: 1-602-233-9166 Fax: 602-936-9164

Issued: 8/7/90
Revised: 9/15/93 - DLS

Call CHEMTREC only in the event of
emergencies during shipping that
involve a spill, leak, fire, or accident
(all calls are recorded)

For Emergencies During Shipping in
the US or Canada, Day or Night,
Call: CHEMTREC 800-424-9300
(Use Chemtrec Company Code "WRR")
For calls from other countries call:
202-483-7616 Collect

Section 1

Generic Name: Electroplating/Metal-Finishing Wastewater Treatment Sludge
Environmental Protection Agency (EPA) Waste Classification: F006
Chemical Family: Metallic (Hydroxide) Precipitates
Synonym: Non-ferrous Metal Hydroxide Filter Cake

PRODUCT - MATERIAL IDENTIFICATION

DOT Shipping Name: RQ, Hazardous waste, solid, n.o.s., (F006)
DOT Hazard Class: 9 Packaging Group III
DOT Identification Number: NA 3077
DOT Emergency Response Guide 31 Applies

Section 2

HAZARDOUS INGREDIENTS

Ingredient:	CAS Number:	Content %:	ACGIH-TLV	Toxicology: (rat, oral)
Copper Hydroxide	20427-59-2	0-30	1.0 mg/m ³ (Dust)	LD-50 1,000 mg/kg
Nickel Hydroxide	12054-48-7	0-15	1.0 mg/m ³ (Dust)	LD-50 1,500 mg/kg
Calcium Hydroxide	1305-62-0	0-15	5.0 mg/m ³ (Dust)	LD-50 7,340 mg/kg
Diatomaceous Earth	68855-54-9	0-10	6.0 mg/m ³ (Dust)	LD-50 3,160 mg/kg

Section 3

PHYSICAL AND REACTIVITY DATA

Description: Solid, Clay-like Clumps,
Gray/Green to Brown,
Water Content 30-80%

Specific Gravity: 1 to 1.4

Solubility: Insoluble in water

Density: 64 to 90 lbs/cu/ft

Incompatible Reactivity: None Known

Vapor Pressure: Insignificant

Stability: Avoid contact with acids

Polymerization: Will not occur

Boiling Point: Above 2600°C

Melting Point: Above 1800°C

pH: 7.0 to 10.0

Odor: Nil

Section 4

FIRE AND EXPLOSION DATA

Flashpoint: Nonflammable

Special Firefighting Procedures: None

Product Decomposition: (Due to Fire or Explosion): None

Oxidation: Non-oxidizing

Explosive: Non-explosive

NFPA
Fire Diamond



Section 5

TOXICITY

Listed Carcinogen component: Nickel

Toxicology: See Sec. 2 (Nickel Hydroxide)

Route of Entry: Inhalation and Ingestion

Section 6

HEALTH EFFECTS AND FIRST AID

Inhalation: Dust may irritate mucous membranes and upper respiratory tract. Remove to fresh air and treat symptoms.

Ingestion: Rare in industry. Induce vomiting (do not induce vomiting or give a liquid to an unconscious person) and call a physician.

Eyes: Dust may irritate eyes. Wash with copious amounts of water for 15 minutes, if effects persist, call a physician.

Skin: Dust may irritate skin, causing forms of eczema. Wash with soap and water.

Long-Term Effects: Chronic overexposure may affect the following target organs or body systems—blood, digestive, respiratory, lungs, liver, kidneys and skin.

Comments: Special attention should be given to employees with anemia, restricted respiratory abilities, lung cancer, permanent kidney damage and metal-sensitive skin or skin lesions.

Section 7

PRECAUTIONS FOR SAFE HANDLING

Handling: Good personal and industrial hygiene should always be practiced. It is recommended that personal protective equipment be used by personnel who will come in contact with the material. The equipment should include eye protection, respirator and gloves.

Storage: Keep covered and avoid conditions where wind could cause dispersal. Do not eat, drink or smoke where material is handled to avoid inhalation or ingestion. Store in a dry area under cover from rain.

Spills: Cleaning procedures should not create excessive dust. Vacuum when possible. Package material and send to World Resources Company at above address.

Section 8

CONTROL MEASURES

Respiratory Protection: NIOSH-MSHA approved respirators as required.

Other Protective Equipment: Coveralls are recommended, but not required.

Eye Protection: Safety Glasses recommended.

Hand Protection: Gloves recommended.

Section 9

GENERATORS VERIFICATION

This MSDS is provided solely for informational purposes and no warranty or responsibility is extended even though reasonable precautions have been taken in the preparation of the data contained for this recyclable material. To the best of my knowledge this MSDS describes the recyclable material listed on the attached Manifest Number: 93007 Telephone: (206) 623-5880 Date: 12/23/93

Company Name and Address: Alaskan Copper Works 628 sixth ave. south
Seattle WA 98134

Signature: _____

AZF-WRC 9/93

AKC-0018328

NOTICE

TO: World Resource Company
8112 West Sherman Street
Phoenix, Arizona 85043

From: Alaskan Copper Works
628 South Hanford Street
Seattle, Washington 98134

SUBJECT: Land Disposal Restriction Notice

Manifest Number: 93007

Date of Shipment: 12/23/93

This shipment of material, which is being provided for recycling, is subject to the land disposal restrictions of 40 CFR, Part 268, Subpart D or the prohibitions specified in 268.32 or RCRA 3004(d). The applicable Land Disposal Restriction Information is provided in accordance with 40 CFR 268.7 and is shown below:

EPA Material Number	Regulated Constituent	Subcategory	Treatability Group	Treatment Standards	
				CFR Reference	Prohibition Level
F006	N/A	N/A	Nonwastewater	40 CFR 268.41 40 CFR 268.43	---

By: Gerald A. Thompson
Alaskan Copper Environmental Assistant

MATERIAL IDENTIFICATION

DOT SHIPPING NAME: Hazardous Waste Solid N.O.S. (F006)
DOT HAZARD CLASS: Class 9
UN OR NA NUMBER: NA 3077

1990
EMERGENCY
RESPONSE
GUIDE

DOT EMERGENCY RESPONSE GUIDE 31

POTENTIAL HAZARDS

FIRE OR EXPLOSION

Some of these material may burn, but none of them ignites readily.

HEALTH HAZARDS

Contact may cause burns to skin and eyes.

Fire may produce irritating or poisonous gases.

Runoff from fire control or dilution water may cause pollution.

EMERGENCY ACTION

Keep unnecessary people away.

Isolate hazard area and deny entry.

Self-contained breathing apparatus (SCBA) and structural firefighters, s protective clothing will provide limited protection.

CALL CHEMTREC AT 1-800-424-9300 FOR EMERGENCY ASSISTANCE.(Use Chemtrec Company Code "WORR") If water pollution occurs, notify the appropriate authorities.

FIRE

Small Fires: Dry chemical, CO2, Halon, water spray or standard foam.

Large fires: Water spray, fog or standard foam is recommended.

Move container from fire area if you can do it without risk.

Do not scatter spilled material with high-pressure water streams.

Dike fire control water for later disposal.

SPILL OR LEAK

Stop leak if you can do it without risk.

Small Dry Spills: With clean shovel place material into clean, dry container and cover, move containers from spill area.

Small spill: Take up with sand or other noncombustible absorbent material and place into containers for disposal.

Large Spills: Dike far ahead of liquid spill for later disposal.

Cover powder spill with plastic sheet or tarp to minimizing spreading.

FIRST AID

In case of contact with material, immediately flush eyes with running water for at least 15 minutes.

Wash skin with soap and water.

Remove and isolate contaminated clothing and shoes at the site.


NOTE: If this response guide is used as an attachment for shipping documents, enter shipping manifest number in block below.

WAD980738546_93007

(Shipping Manifest Number)

Recyclable Material

US DOT Description	Container		Quantity	Unit	Waste No.
	No.	Type			
RQ, Hazardous waste solid, n.o.s (F006), 9, NA3077, III	5	CF	6,577	lbs	F006
Total Quantity			6,577		

Weighed
By: 

Verified
By: 